

TATTOO

Plastic Card Printer



Latest birth from Evolis product range, the **Tattoo** printer is a mixture of technology and innovation. Hi-Tech Design, compactness and ease of use, the **Tattoo** revolutionizes the world of monochrome printing on plastic cards. Within seconds, the **Tattoo** personalizes in monochrome your pre-printed or blank plastic cards. It prints your high resolution text, bar codes, graphics and logos.

Compact, yet elegant

The **Tattoo** melts perfectly into your environment. It owes its extreme compactness to the Lift Card system which allows the passage of cards on two levels. A completely new system, designed by the Evolis R&D department. Autonomous, it can also function without a computer, simply connected to a keyboard. Enter your data (name, number, bar code, encoding) and print your cards completely independently. This innovative design is ideal for point of sale and exhibition receptions.

Easy to use, yet powerful

Innovating, the **Tattoo** is equipped with an ingenious process of detachable card feeders. A technology allowing several series of cards to be prepared at the same time. A solution all the more revolutionary since an automatic gauge system analyses the thickness of the cards during each card feeder change. Completely enclosed, the card feeder is dust proof and thus guarantees an optimal card printing quality.

Astute, the **Tattoo** offers a double operating mode simultaneously: Card by card manual feeding from the front mouth and automatic feeding with the 100 cards feeder from the back.

Ergonomic, its opening system allows a direct access to the inside of the printer and thus makes the installation of consumables very easy and quick. The print head can be replaced in a few seconds by the operator without any tool or adjustment thanks to its Push & Twist concept.

Tech, yet economic

Its price positioning and its cost per printed card make the **Tattoo** the best quality / price ratio on the market of monochrome plastic card printers.

Printing Mode	Monochrome Thermal Transfer in Line Mode or Diffusion Mode
Printer specification	Integrated Ribbon Saver
Printing speed	500 cards/hour
Resolution	300 dpi
Windows drivers	Windows 95/98/Me/NT4.0/200 and XP
Warranty	Printer: 1 year Print head: 1 year, unlimited number of prints*1
Ribbon Type	Mono Color Ribbon: 500 cards/roll Colors available: black, blue, red, green, white, gold, silver, scratch off
Card loading modes	Manual feeding or automatic feeding
Options	USB port (cable supplied) Serial port available on demand Additional interchangeable card feeder
Other printer models	Tattoo Mag Printer with HICO/LOCO magnetic stripe encoder - ISO 7811 Tattoo Stand-Alone Printer connected to a keyboard, available upon study

1 - Clause governing the use of Evolis consumables

Other specifications

Programming Language ePL
Card types: All PVC, Composite Polyester and ABS cards
Card format: ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm)
Card thickness: from 0,25 mm (10 mil) to 0.76 mm (30 mil)
Card feeder capacity: 100 cards (0,76 mm-30 mil) - 300 cards (0,25 mm-10 mil)
Printer size:
- Height: 166 mm X Width: 290 mm X Depth: 187 mm
Printer weight: 2,5 kg (5.5lbs)
Communication interface: Centronics Parallel (cable supplied)
Electrical: 110~230 Volts CA, 60~50 Hertz
Environmental:
- Min / Max operating temperatures: 15°C / 30°C
- Humidity: 20% to 65% non-condensing
- Min / Max storage temperatures: -5°C / +70°C
- Storage humidity: 20% to 70% non-condensing
- Operating ventilation: free air.



Securetech Peripherals, Inc.,
336 N. Gaffey Street 2nd Floor
San Pedro, CA 90731 U.S.A.

<http://securetech-corp.com>
sales@securetech-corp.com
Phone : 310-547-8501, Fax : 310-521-9600